





EDMONTON
ALBERTA
CALGARY
ALBERTA
SURREY
BC
WINNIPEG
MANITOBA

10519 114 ST
T5H 3J6
726 42 Ave.S.E.
T2G 5N4
#9 8285 132ND ST.
V3W 4N6
1499 ST. JAMES ST.
R3H 0W9

P (780) 423-4066
F (780) 425-8579
P (403) 243-4130
F (403) 243-0552
P (604) 590-1667
F (604) 590-5501
P (204) 775-8848
F (204) 779-4391



AO Smith + Century Brand



Above Ground Swimming Pool Pump Motors - Thru Bolt Mount

Century Flex 48 W/Stainless Steel Shaft – Ball Bearing – “1081” – “1795” – “1563” – Rigid Base

| HP | RPM | VOLTS | AMPS | S.F. | FRAME | SHAFT | PART# |
|-----|------|---------|-----------|------|-------|----------|--------|
| 1/2 | 3600 | 115 | 7.2 | 1.0 | 48Y | Threaded | BN23SS |
| 3/4 | 3600 | 115 | 9.8 | 1.0 | 48Y | Threaded | BN24SS |
| 1 | 3600 | 115 | 12.0 | 1.0 | 48Y | Threaded | BN25SS |
| 1.5 | 3600 | 115/230 | 16.0/8.0 | 1.0 | 48Y | Threaded | BN35SS |
| 2 | 3600 | 115/230 | 20.0/10.0 | 1.0 | 48Y | Threaded | BN40SS |

Century Flex 48 LASAR Line – Low Amp Start & Run – “1081” – “1563” – Rigid Base

| | | | | | | | |
|----------|-----------|-----|----------|-----|-----|----------|------|
| 3/4-0.10 | 3600/1800 | 115 | 8.8/2.6 | 1.0 | 48Y | Threaded | BN36 |
| 1-0.12 | 3600/1800 | 115 | 11.0/2.9 | 1.0 | 48Y | Threaded | BN37 |
| 1.5-0.25 | 3600/1800 | 115 | 16.4/4.4 | 1.0 | 48Y | Threaded | BN50 |
| 1.5-0.18 | 3600/1800 | 230 | 8.0/2.6 | 1.0 | 48Y | Threaded | BN34 |
| 2-0.25 | 3600/1800 | 230 | 10.5/2.6 | 1.0 | 48Y | Threaded | BN51 |

Century Flex 48 LASAR-XL – Extra Low Running Amps – Rigid Base

| | | | | | | | |
|----------|-----------|-----|----------|-----|-----|----------|------|
| 1-0.12 | 3600/1800 | 115 | 10.3/3.1 | 1.0 | 48Y | Threaded | BN38 |
| 1.5-0.18 | 3600/1800 | 115 | 13.8/3.8 | 1.0 | 48Y | Threaded | BN60 |
| 2-0.25 | 3600/1800 | 230 | 8.5/2.8 | 1.0 | 48Y | Threaded | BN61 |
| 3-0.38 | 3600/1800 | 230 | 12.0/3.5 | 1.0 | 48Y | Threaded | BN62 |
| 4-.42SPL | 3600/1800 | 230 | 12.0/3.5 | 1.0 | 48Y | Threaded | BN63 |

Square Flange Pool Filter Motors

High Service Factor – 50 Degree Ambient – Ball Bearing - Dripproof


| | | | | | | | |
|-----|------|---------|----------|------|-----|----------|----------|
| 1/3 | 3600 | 115/230 | 9.9/5.0 | 1.95 | 48Y | Threaded | SQ1032 |
| 1/2 | 3600 | 115/230 | 13.4/6.7 | 1.9 | 48Y | Threaded | SQ1052 |
| 3/4 | 3600 | 115/230 | 15.3/7.6 | 1.65 | 48Y | Threaded | SQ1072 |
| 1 | 3600 | 115/230 | 19.2/9.6 | 1.65 | 48Y | Threaded | SQ1102 |
| 1.5 | 3600 | 230 | 10.4 | 1.47 | 48Y | Threaded | SQ1152 |
| 2 | 3600 | 230 | 11.2 | 1.3 | 48Y | Threaded | SQ1202 |
| 3 | 3600 | 230 | 15.4 | 1.15 | 56Y | Threaded | SQ1302V1 |



EDMONTON
ALBERTA
CALGARY
ALBERTA
SURREY
BC
WINNIPEG
MANITOBA

10519 114 ST
T5H 3J6
726 42 Ave.S.E.
T2G 5N4
#9 8285 132ND ST.
V3W 4N6
1499 ST. JAMES ST.
R3H 0W9

P (780) 423-4066
F (780) 425-8579
P (403) 243-4130
F (403) 243-0552
P (604) 590-1667
F (604) 590-5501
P (204) 775-8848
F (204) 779-4391



Square Flange Pool Filter Motors

Low Service Factor – 50 Degree Ambient – Ball Bearing - Dripproof

| HP | RPM | VOLTS | AMPS | S.F. | FRAME | SHAFT | PART# |
|-----|------|---------|----------|------|-------|----------|---------|
| 1/2 | 3600 | 115/230 | 9.9/5.0 | 1.3 | 48Y | Threaded | USQ1052 |
| 3/4 | 3600 | 115/230 | 13.4/6.7 | 1.27 | 48Y | Threaded | USQ1072 |
| 1 | 3600 | 115/230 | 15.3/7.6 | 1.25 | 48Y | Threaded | USQ1102 |
| 1.5 | 3600 | 115/230 | 19.2/9.6 | 1.1 | 48Y | Threaded | USQ1152 |

Square Flange Pool Motors

High Service Factor – 50 Degree Ambient – Dripproof

| | | | | | | | |
|---------|-----------|-----|----------|------|-----|----------|----------|
| 3/4-1/8 | 3600/1800 | 230 | 6.1/2.1 | 1.6 | 48Y | Threaded | SQS1072R |
| 1-1/6 | 3600/1800 | 230 | 9.5/2.5 | 1.65 | 48Y | Threaded | SQS1102R |
| 1.5/1/4 | 3600/1800 | 230 | 10.0/3.0 | 1.47 | 48Y | Threaded | SQS1152R |
| 2-1/3 | 3600/1800 | 230 | 11.3/3.3 | 1.3 | 48Y | Threaded | SQS1202R |

NEMA C Flange Jet Pump Motors

High Service Factor – 778 Design – Sealed Switch design – Ball Bearing - Dripproof


| | | | | | | | |
|-----|------|---------|-----------|-----|-----|----------|-------|
| 1/3 | 3600 | 115/230 | 8.6/4.3 | 1.8 | 56C | Keyed | K1032 |
| 1/3 | 3600 | 115/230 | 8.6/4.3 | 1.8 | 56J | Threaded | T1032 |
| 1/2 | 3600 | 115/230 | 10.8/5.4 | 1.6 | 56C | Keyed | K1052 |
| 1/2 | 3600 | 115/230 | 10.8/5.4 | 1.6 | 56J | Threaded | T1052 |
| 3/4 | 3600 | 115/230 | 14.8/7.4 | 1.5 | 56C | Keyed | K1072 |
| 3/4 | 3600 | 115/230 | 14.8/7.4 | 1.5 | 56J | Threaded | T1072 |
| 1 | 3600 | 115/230 | 16.2/8.1 | 1.4 | 56C | Keyed | K1102 |
| 1 | 3600 | 115/230 | 16.2/8.1 | 1.4 | 56J | Threaded | T1102 |
| 1.5 | 3600 | 115/230 | 22/11 | 1.3 | 56C | Keyed | K1152 |
| 1.5 | 3600 | 115/230 | 22/11 | 1.3 | 56J | Threaded | T1152 |
| 2 | 3600 | 115/230 | 22.6/11.3 | 1.2 | 56C | Keyed | K1202 |
| 2 | 3600 | 115/230 | 22.6/11.3 | 1.2 | 56J | Threaded | T1202 |



EDMONTON
ALBERTA
CALGARY
ALBERTA
SURREY
BC
WINNIPEG
MANITOBA

10519 114 ST
T5H 3J6
726 42 Ave.S.E.
T2G 5N4
#9 8285 132ND ST.
V3W 4N6
1499 ST. JAMES ST.
R3H 0W9

P (780) 423-4066
F (780) 425-8579
P (403) 243-4130
F (403) 243-0552
P (604) 590-1667
F (604) 590-5501
P (204) 775-8848
F (204) 779-4391



NEMA C Flange Pool Filter Motors

High Service Factor – “1081” Design – Sealed Switch Design – Ball Bearing - Drip-proof

| HP | RPM | VOLTS | AMPS | S.F. | FRAME | SHAFT | PART# |
|---------|-----------|-------|----------|------|-------|----------|----------|
| 3/4-1/8 | 2600/1800 | 230 | 6.4/1.9 | 1.5 | 56J | Threaded | STS1072R |
| 1-1/6 | 3600/1800 | 230 | 8.5/2.5 | 1.5 | 56J | Threaded | STS1102R |
| 1.5-1/4 | 3600/1800 | 230 | 9.0/3.3 | 1.3 | 56J | Threaded | STS1152R |
| 2-1/3 | 3600/1800 | 230 | 11.4/4.1 | 1.2 | 56J | Threaded | STS1202R |

NEMA C Flange Pool Filter Motors

High Service Factor - “1081” Design – Sealed Switch Design – Ball Bearing – Drip-proof

| | | | | | | | |
|-----|------|---------|----------|------|-----|----------|--------|
| 1/2 | 3600 | 115/230 | 10.6/5.3 | 1.6 | 56C | Keyed | SK1052 |
| 1/2 | 3600 | 115/230 | 11.0/5.5 | 1.6 | 56J | Threaded | ST1052 |
| 3/4 | 3600 | 115/230 | 14.6/7.3 | 1.5 | 56C | Keyed | SK1072 |
| 3/4 | 3600 | 115/230 | 15.0/7.5 | 1.5 | 56J | Threaded | ST1072 |
| 1 | 3600 | 115/230 | 17.0/8.5 | 1.5 | 56C | Keyed | SK1102 |
| 1 | 3600 | 115/230 | 18.6/9.3 | 1.5 | 56J | Threaded | ST1102 |
| 1.5 | 3600 | 115/230 | 19.4/9.7 | 1.3 | 56C | Keyed | SK1152 |
| 1.5 | 3600 | 115/230 | 19.6/9.8 | 1.3 | 56J | Threaded | ST1152 |
| 2 | 3600 | 230 | 11.2 | 1.3 | 56C | Keyed | SK1202 |
| 2 | 3600 | 230 | 11.4 | 1.3 | 56J | Threaded | ST1202 |
| 3 | 3600 | 230 | 14.4 | 1.15 | 56C | Keyed | SK1302 |
| 3 | 3600 | 230 | 13.8 | 1.15 | 56J | Threaded | ST1302 |

NEMA C Flange Pool and Spa Pump Motors

High Service Factor – “1081” Design – Switchless – Ball Bearing - Drip-proof

| | | | | | | | |
|-----|------|---------|----------|-----|-----|----------|------|
| 1/2 | 3600 | 115/230 | 8.8/4.4 | 1.6 | 56C | Keyed | B120 |
| 1/2 | 3600 | 115/230 | 8.8/4.4 | 1.6 | 56J | Threaded | B126 |
| 3/4 | 3600 | 115/230 | 12.0/6.0 | 1.5 | 56C | Keyed | B121 |
| 3/4 | 3600 | 115/230 | 12.0/6.0 | 1.5 | 56J | Threaded | B127 |
| 1 | 3600 | 115/230 | 14.4/7.2 | 1.4 | 56C | Keyed | B122 |
| 1 | 3600 | 115/230 | 14.4/7.2 | 1.4 | 56J | Threaded | B128 |
| 1.5 | 3600 | 115/230 | 18.4/9.2 | 1.3 | 56C | Keyed | B123 |
| 1.5 | 3600 | 115/230 | 18.4/9.2 | 1.3 | 56J | Threaded | B129 |
| 2 | 3600 | 230 | 10.5 | 1.2 | 56C | Keyed | B124 |
| 2 | 3600 | 230 | 10.5 | 1.2 | 56J | Threaded | B130 |